

ELECTRIC SCISSOR LIFTS - ELECTRIC DRIVE

# 0608ME AC (1932ME)

Compliant with AS 1418 · 10 standards

## PRODUCT HIGHLIGHTS

### Efficient and Environmentally Friendly

- Higher work efficiency
- Environmental protection, zero emissions

### Reduced Maintenance Costs

- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts

### Reliable Performance

- Bumper rail protection



#### Standard Features

2WD×2WS	AGM maintenance-free battery	Telematic ready
Non-marking tires	Proportional control	Battery isolator
Emergency stop	Forklift pockets and lifting points	Secondary guarding system
Flashing beacon	Automatic pothole protection	White noise alarm
Foldable guardrail	Bumper rails	Fault diagnosis system
Drivable at full height	Weight management system	Manual storage box

#### Options & Accessories

Wheel nut indicators	Panel lifting system	Telematic device
Fire extinguisher/Bracket	Mine spec	AC power to platform
Pipe lifting system		

**SINOBOOM™**

**PARTNERS IN ACCESS™**

🌐 [SINOBOOM.AU](http://SINOBOOM.AU) | 📞 03 8905 1550

HO: BRISBANE – 39 ALTA ROAD, CABOOLTURE QLD 4510 | SYDNEY – 1/3 VOYAGER CT, GLENDENNING NSW 2761  
MELBOURNE – 32-34 MARNI, DANDENONG SOUTH VIC 3175

**ELECTRIC SCISSOR LIFTS - ELECTRIC DRIVE**

**0608ME AC (1932ME)**

Compliant with AS 1418 · 10 standards

Model	0608ME AC (1932ME)
<b>Dimensions</b>	
Max Working Height (Indoor/Outdoor)	7.8 m (25'7")
A Max Platform Height (Indoor/Outdoor)	5.8 m (19')
B Max Horizontal Extension	0.9 m (3')
C Length-Stowed	1.8 m (5'11")
D Width-Stowed	0.81 m (2'8")
E Height-Stowed (Rail Folded)	1.88 m (6'2")
E Height-Stowed (Rail Unfolded)	2.00 m (6'56")
F Wheelbase	1.334 m (4'4")
Ground Clearance (Pothole Guard Stowed)	0.075 m (3")
Ground Clearance (Pothole Guard Deployed)	0.019 m (0.75")
Platform Dimensions (L×W×H)	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")
<b>Performance</b>	
Platform Capacity	230 kg (507 lbs)
Extension Platform Capacity	120 kg (265 lbs)
Platform Occupants (Indoor/Outdoor)	2 persons/1 person
Drive Speed (Stowed)	0~4 km/h (0~2.5 mph)
Drive Speed (Raised)	0~0.5 km/h (0~0.31 mph)
Lift Time (Rated Load)	15 s~20 s
Lower Time (Rated Load)	25 s~30 s
Gradeability	25%
Max Allowable Inclination (front-to-back/side-to-side)	3° /1.5°
Turning Radius (Inside/Outside)	0/1.49 m (0/4'10.7")
Tyre Size/Type	323×100 mm (12.7×4")/solid
<b>Power</b>	
Drive×Steer	2 WD×2 WS
Power Source (V/kW)	24 V/2.2 kW
Drive Motor (V/kW)	24 V AC/0.6 kW
Hydraulic Tank Capacity	6 L (1.3 gal (UK)/ 1.6 gal (US))
Batteries	24 V,220 Ah,20 hr (AGM) 25.6 V,156 Ah,1 hr (Lithium battery)
Charger (Input/Output)	100~240V AC/30 A
<b>Weight</b>	
Weight (Indoor/Outdoor)	1,575 kg (3,473 lbs)
Standards Compliance	AS 1418 · 10

