

ELECTRIC ROUGH TERRAIN SCISSOR LIFTS

1018RE (3369RE)

Compliant with AS 1418 · 10 standards

PRODUCT HIGHLIGHTS

Excellent Performance

- Up to 35% gradeability, easily handling outdoor needs

High Efficiency

- 1.6m(5'3") wide platform with one-way extension platform
- One-click leveling, easy work on uneven road surfaces

Easy Maintenance

- Two-sided hatchback door design, for convenient maintenance
- Self-diagnose system display alarm

Green

- Comfortable working environment without noise pollution
- Meet indoor or emissions-critical site requirements

Economical

- Battery quality assurance, low failure rate and reduced maintenance costs compared with diesel power, which reduces overall operating cost



Standard features

2WD×2WS	Oscillating axle	Telematic ready
Non-marking tires	Forklift pockets and lifting points	Battery isolator
Emergency stop	Proportional control	Secondary guarding system
Flashing beacon	Emergency lowering system	White noise alarm
Manual storage box	weight management system	Lithium Batteries

Options & Accessories

Wheel nut indicators	Panel lifting system	Telematic device
Fire extinguisher/Bracket	Mine spec	AGM maintenance-free battery
Pipe lifting system	AC power to platform	Platform work light

SINOBOOM™

PARTNERS IN ACCESS™

🌐 SINOBOOM.AU | 📞 03 8905 1550

HO: BRISBANE – 39 ALTA ROAD, CABOOLTURE QLD 4510 | SYDNEY – 1/3 VOYAGER CT, GLENDENNING NSW 2761

MELBOURNE – 32-34 MARNI, DANDENONG SOUTH VIC 3175

ELECTRIC ROUGH TERRAIN SCISSOR LIFTS

1018RE (3369RE)

Compliant with AS 1418 · 10 standards

Model	1018RE (3369RE)
Dimensions	
Max Working Height	12 m (39'4.4")
A Max Platform Height	10 m (32'9.7")
B Max Horizontal Extension	1.5 m (4'11.1")
C Length-Stowed (Outriggers)	3.8 m (12'5.6")
D Width-Stowed	1.77 m (5'9.7")
E Height-stowed (Rail Folded)	1.96 m (6'5.2")
E Height-stowed (Rail Unfolded)	2.59 m (8'6")
F Wheelbase	2.28 m (7'5.8")
Ground Clearance	0.22 m (8.66")
Platform Dimensions (L×W×H)	2.8 m×1.6 m×1.1 m (9'2"×5'3"×3'7")
Performance	
Platform Capacity	450 kg (992 lbs)
Extension Platform Capacity	140 kg (309 lbs)
Platform Allowable Occupants (Indoor/Outdoor)	4 persons/2 persons
Drive Speed (Stowed)	0~6 km/h (0~3.7 mph)
Drive Speed (Raised)	0~0.48 km/h (0~0.3 mph)
Lift Time (Unloaded)	42 s~52 s
Lower time (Unloaded)	40 s~50 s
Gradeability	35 %
Tilt Rating (Front to Back)	3°
Tilt Rating (Side to Side, Outrigger Retred/Extend)	2° /0.8°
Max Outrigger Leveling (Front to Back)	5.3° (front)/4.2° (back)
Max Outrigger Leveling (Side to Side)	11.7°
Turning Radius (Inside/Outside)	2.11 m/4.6 m (6'11"/15'1")
Tire Size/Type	26×12-16.5/Solid foam filled
Power	
Drive × Steer	2 WD×2 WS
Batteries	48 V, 390 Ah
Hydraulic Tank Capacity	72 L (15.8 gal (UK)/19 gal (US))
System Voltage	48 VDC
Weight	
Weight (Outriggers/Without Outriggers)	4,510 kg (9,943 lbs) / 4,050 kg (8,929 lbs)
Standards Compliance	AS 1418 · 10

